ADDROVATION OCCUMENTS	© Co	terial Compo pyright 2005. IPC, Bannoc ternational and Pan-Ameri	kburn, Illinois	. All rights reserve	tion with lower	level pa	arts, the o	declaratio	n encompa	asses all low	er level mate	erials for wh	e: if the item is a hich the manuf this declaration	acturer has		
1752-2 1.1	•	Web Site for Informat		-1752 Standa	rd					ration Class * 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informat						
Supplier Information																
Company Name *		Company Unique ID		Unique ID Authority			Response Date *			Response Document ID						
SEMTECH CORPORATION	SEMTECH CORPOR	RATION			2016-0	6-29										
Contact Name * Title - Contact				Phone - Contact *			Contact	t *								
Elvia Finkel Specialist, Documen			t Control/C	rol/C 805-498-2111			@semte	ch.com		Duplicate Contact -> Authorized Representative						
Authorized Representative * Title - Representative			Э	Phone - Representative *			Represe	entative	* Su	Supplier Comments or URL for Additional Information						
Elvia Finkel Specialist, Docu			t Control/C	trol/C 805-498-2111			@semte	ch.com								
Requester Item Number		Mfr Item Number		Mfr Item Name		Effective	tive Date Version Manuf		Manufactu	ring Site	Weight *	UOM	Unit Ty	ре		
		GS1672-IBE3		HD/SD-SDI S	Korea			Korea	a 385.9		mg	Each				
Alternate Recommenda	ation				Alternate Item Co			Item Comr	omments							
Manufacturing Process Information																
Terminal Plating / Grid Array Material			Terminal Ba	ase Alloy	ting Peak Process Body Tempe			Temperatu	erature Max Time at Peak Temperature Number of Reflow Cy							
Tin/Silver/Copper (Sn/Ag/Cu)					260 (260 C	30 seconds 3							
Comments GS1672-IBE3 is a REACH	-con	npliant product, per	EU Regul	ation EC1907	7/2006 to include	recent	addition	of SVH	C candida	ate list of su	bstances D	December 2	2015			

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type *** Detailed Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a ?RoHS restricted substance?) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier?s liability and the Company?s remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply. 1 - Item(s) does not contain RoHS restricted substances per the definition above Supplier Acceptance * Accepted **RoHS Declaration *** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature**

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

Item/SubItem			Homogeneous	Weight	Unit of		Laval	Substance Category			Substance	CAS	Evennt	Weight	Unit of	Tolerance		PPM
	Name		Material	weight	Measure		Level	Substance Category			Substance	CAS	Exempt	weight	Measure	-	+	PPIVI
+1 -1	Substrate	+M -M	вт	159.84	mg	+C -C	Supplier		+S	-S	SiO2	7631-86-9		17.023	mg		ı	106,50
									+S	-s	Acrylic	Proprietary		15.984	mg			100,00
									+S	-s	Ероху	Proprietary		12.787	mg			80,000
									+S	-S	Bisphenol	Proprietary		23.976	mg			150,00
									+S	-s	Triazol	Proprietary		27.972	mg			1,750,0
									+S	-S	Cu	7440-50-8		58.821	mg			368,00
									+S	-S	Ni	7440 02 0		2.398	mg			15,000
		_							+S	-s	Au	7440-57-5		0.879	mg			5,500
+1 -1	Mold Compound	+M -M	KE-G1250	159.24	mg	+C -C	Supplier		+S	-S	Silica (fused)	60676-86-0		140.131	mg			880,00
									+S	-s	Epoxy Resin	Proprietary		9.554	mg			60,000
									+S	-s	Phenolic Resin	Proprietary		8.758	mg			55,000
									+S	-s	Carbon Black	1333-86-4		0.796	mg			5,000
+1 -1	Chip 1	+M -M		7.59	mg	+C -C	Supplier		+S	-S	Si	7440-21-3		7.491	mg			987,00
		_							+S	-s	AI	7429-90-5		0.046	mg			6,000
									+S	-S	w	7440-33-7		0.03	mg			4,000
									+S	-S	ті	7440-32-6		0.023	mg			3,000
+1 -1	Chip 2	+M -M		1.81	mg	+C -C	Supplier		+S	-S	Si	7440-21-3		1.786	mg			987,10
									+S	-s	AI	7429-90-5		0.011	mg			6,000
									+S	-s	w	7440-33-7		0.007	mg			4,000
		_							+S	-s	ті	7440-32-6		0.005	mg			3,000
+1 -1	Die Attach	+M -M	2100A	5.15	mg	+C -C	Supplier		+S	-S	Ag	7440-22-4		3.966	mg			770,00
									+S	-s	Epoxy Resin	Proprietary		0.335	mg			65,000
									+S	-s	Functionalized Resin	Proprietary		0.335	mg			65,000

	+	S -S Diester		Proprietary	0.515	mg		100,00				
+I -I Wire	+M -M	3.69	mg	+C -C Supplier	·	+S	-s	Au	7440-57-5	3.69	mg	999,90
+I -I Solder Balls	+M -M	48.64	mg	+C -C Supplier		+S	-S	Sn	7440-31-5	46.451	mg	955,00
						+S	-s	Ag	7440-22-4	1.946	mg	40,000
						+S	-s	Cu	7440-50-8	0.243	mg	5,000