	© Co	terial Compo pyright 2005. IPC, Bannoc International and Pan-Americ	kburn, Illinois	. All rights reserve	tion with lower	level p	arts, the	declaratior	n encor	mpasses a	all lower	level mate	erials for	which t	e item is an assembly he manufacturer has declaration.
1/32-2 1.1		Web Site for Informat //www.ipc.org/IPC-1	rd		n Type * Declaration Class * ibute Class 6 - RoHS Yes/No, Homogeneous Materials and M							s and Mfg Informat			
Supplier Information															
Company Name *		Company Unique ID		Unique ID Au	thority	Respo	onse Date	e *		Respons	e Docum	nent ID			
SEMTECH CORPORATIO	SEMTECH CORPORATION 00-847-9941			DUNS		2016-03-29									
Contact Name * Roya Motamedi	Title - Contact QA Customer Servic	e Specialis	Phone - Con 805-498-211		Email - Contact * rmotamedi@semtech			om	Duplicate Contact -> Authorized Representativ			epresentative			
Authorized Representati Roya Motamedi	Authorized Representative * Title - Representative Roya Motamedi QA Customer Service Speci			-	resentative * 1		Email - Representative * Su rmotamedi@semtech.com			Supplier	Commei	nts or URL	for Add	litional I	nformation
Requester Item Number	r	Mfr Item Number		Mfr Item Name		Effective Date Vers		Version	Manufa	acturing Site Weig		Weight *	UC	M	Unit Type
		RClamp3324P.TNT		Low Capacitance RClamp® 4-L							:	3.469		J	Each
Alternate Recommenda	ation								Iternate Item Co		omments				
Manufacturing Proces	ss In	formation													
Terminal Plating / Grid Array I	Materi	al	Terminal Ba	ase Alloy	J-STD-020 MSL Ra	iting	Peak Proc	ess Body	Temper	rature Max	x Time at	Peak Temp	perature	Number	of Reflow Cycles
Nickel/Palladium/Gold (Ni/Pd/Au) CU Alloy				1			260 C		;	30 s		conds	3		
Comments RClamp3324P.TNT is RE	ACH	-compliant product,	per EU R	egulation EC	1907/2006 to incl	ude re	cent add	ition of S	WHC o	andidate	e list of s	substance	es in De	cembe	r 2015.

Save the fields in this form to a file	Evport Data	Import fields from a file into this form	Import Data	Clear all of the fields on this form	Reset Form	Lock the fields on this form to prevent chan	Look Cupplier Fields							
RoHS Materia	RoHS Material Composition Declaration Declaration Declaration Type * Detailed													
		ty limit of 0.1% by mass (100 Ethers (PBDE) and quantity					ominated Biphenyls (PBB),							
chromium, polybromina excess of an applicable gathered the information Company will rely on thi completing this form, ar certifications regarding conditions of that agree	ted biphenyls and/or polybrominate quantity limit, please indicate below it provides in this form using app s certification in determining the co d that Supplier may not have inde heir contributions to the part, and ment, including any warranty rights	ompliance of its products with European pendently verified such information. Ho those certifications are at least as comp	ricted substance?) in excess believe may apply. If the p y and that such information n Union member state laws owever, in situations where prehensive as the certificati hat agreement, will be the s	ss of the applicable quantity lim part is an assembly with lower I is true and correct to the best of that implement the RoHS Dire Supplier has not independently ion in this paragraph. If the Co sole and exclusive source of the	it identified above. If a homoge evel components, the declaration of its knowledge and belief, as of ctive. Company acknowledges y verified information provided lo popany and the Supplier enter is a Supplier?s liability and the Co	eneous material within the part cor on shall encompass all such comp of the date that Supplier complete: s that Supplier may have relied on by others, Supplier agrees that, at into a written agreement with resp impany?s remedies for issues that	ntains a RoHS restricted substance in ponents. Supplier certifies that it s this form. Supplier acknowledges that information provided by others in a minimum, its suppliers have provided							
RoHS Declaration	n * 1 - Item(s) does not conta	ain RoHS restricted substances per the	he definition above			Supplier Acceptance *	Accepted							
	e declared item does not co all applicable exemptions.	ntain RoHS restricted substanc	es per the definition a	above except for defined	RoHS exemptions, then	select the corresponding re	esponse in the RoHS Declaration							
Declaration S	ignature													
In a family of the second	ward a factor and the factor of the second s	al Calaba and all manages of the last		a second se	• • • • •	and the second sec	terrestring and - Distingthe stars							

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

	Item/SubItem		Homogeneous	Weight	Unit of		Level	Substance Category			Substance	CAS	Exempt	Weight	Unit of	Toler	ance	PPM
	Name		Material		Measure										Measure	-	+	
+ -	Die	+M -M	Doped silicon	0.02789	8mg	+C -C	Supplier		+S		Si	7440-21-3		0.0257	mg			7,407
									+S	-S	AI	7429-90-5		0.0022	mg			56,211
+ -	Lead frame	+M -M	SGP2510P8 Sub	s1.33938	9mg	+C -C	Supplier	CCL-HL832NX Core N	+S	-S	Bismaleimide Triazine r	105391-33-1		0.196	mg			56,505
		_							+S	-s	Inorganic Filler	21645-51-2		0.098	mg			28,253
									+S	-s	Continuous Filament Fi	65997-17-3		0.196	mg			56,505
									+S	-s	Copper	7440-50-8		0.49	mg			141,26
						+C -C	Supplier	PSR-4000 Solder Mas	+S	-s	Acrylic Esters	26376-86-32		0.1137	mg			32,791
								I	+S	-s	Organic black dye	Proprietary		0.0019	mg			549
									+S	-s	Barium Sulfate	7727-43-7		0.1148	mg			33,108
									+S	-s	Talc	14807-96-6		0.0096	mg			2,770
									+S	-s	Silica crystalline	7631-86-9		0.0099	mg			2,842
									+S	-s	Activator	Proprietary		0.0199	mg			5,740
									+S	-s	Amine compound	Proprietary		0.0012	mg			342
									+S	-s	Defoamer	Proprietary		0.0086	mg			2,471
									+S	-s	Dipropyl glycol dinitrate	112-15-2		0.0382	mg			11,024
									+S	-s	Heavy aromatic solvent	64742-94-5		0.0392	mg			11,314
									+S	-s	Naphthalene	91-20-3		0.0023	mg			657
		+M -M	NiPdAu plating	0.10391	8mg	+C -C	в		+S	-s	Nickel	7440-02-0		0.0087	mg			2,497
						+C -C	Supplier	middle plating	+S	-S	Pd	7440-05-3		0.0852	mg			24,549
						+C -C	Supplier	outer plating	+S	-s	Au	7440-57-5		0.0101	mg			2,913
+ -	Bonding wire	+M -M	CuPd	0.01220	3mg	+C -C	Supplier		+S	-S	Cu	7440-50-8		0.0119	mg			3,430
	_						۹	1	+S	-s	Pd	7440-05-3		0.0003	mg			88
+ -	Molding compound	d +M -M	EME-G760L	1.86715	8mg	+C -C	Supplier		+S	-S	Silica (Amorphous) A	60676-86-0	1	1.5333	mg			442,04

	+S	-S	Silica (Amorphous) B	7631-86-9	0.1583	mg		45,6	30
	+S	-S	Epoxy resin	Proprietary	0.1583	mg		45,6	30
	+S	-S	Phenol resin	9003-35-4	0.0594	mg		17,1	11
	+S	-S	Metal Hydroxide	Proprietary	0.0594	mg		17,1	11
	+S	-S	Carbon Black	1333-86-4	0.0023	mg		2,85	2
+I -I Die attached epoxy +M -M 8006	NS		0.00684 mg +0	C -C Supplier		+S	-S	Aluminum (Oxi

+S	-S	Aluminum Oxide	1344-28-1	0	0.0023	mg		670
+S	-S	Diethylene glycol mono	112-15-1	C	0.0023	mg		670
+S	-S	Epoxy resins	Proprietary	C	0.0019	mg		552
+S	-S	Amine	Proprietary	C	0.0003	mg		79