1 GOOGLATION GONALEGTING	© Cop	terial Compo pyright 2005. IPC, Bannocl ternational and Pan-Americ	kburn, Illinois	All rights reserv	tion with lower	level	parts, the	declaratio	n encoi	mpasses all low	er level mate	erials for whi	if the item is an assemblich the manufacturer ha		
1/32-2 1.1	IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x						m Type * tribute			ation Class * - RoHS Yes/N	ss * /es/No, Homogeneous Materials and Mfg Informat				
Supplier Information															
Company Name * Company Unique ID				Unique ID Authority			Response Date *			Response Document ID					
SEMTECH CORPORATION 00-		00-847-9941		DUNS			01-03								
Contact Name *		Title - Contact		Phone - Contact *			Email - Contact *			D lianta	0	A tl	d Damma antation		
Roya Motamedi		Supervisor, QA Prod	uct Suppoi	805-498-2111			rmotamedi@semtech.com			Duplicate Contact -> Authorized Representative					
Authorized Representative * Title - Re		Title - Representative)	Phone - Representative *			l - Repres	entative	*	Supplier Comments or URL for Additional Information					
Roya Motamedi Supervisor, QA P			uct Suppo	805-498-211	1	rmota	amedi@s	emtech.c	om						
Requester Item Number		Mfr Item Number		Mfr Item Name	•	Effecti	ve Date	Version	Manufa	acturing Site	Weight *	UOM	Unit Type		
		RClamp3382P.TCT		Low Capacitance RailClamp 2-					China		2.253	mg	Each		
Alternate Recommendation						Alternate Item C			omments		·				
Manufacturing Proces	s Inf	formation													
Terminal Plating / Grid Array Material Terminal B			Terminal Ba	Base Alloy J-STD-020 MSL Ra			ating Peak Process Body Temp			ature Max Time	nber of Reflow Cycles				
Nickel/Palladium/Gold (Ni/Pd/Au) CU A			CU Alloy	y 1							30 se	econds 3			
Comments					I		1			I					

RClamp3382P.TCT is REACH-compliant product, per EU Regulation EC1907/2006 to include recent addition of SVHC candidate list of substances in June 2016.

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type *** Detailed Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a ?RoHS restricted substance?) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier?s liability and the Company?s remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply. 1 - Item(s) does not contain RoHS restricted substances per the definition above Supplier Acceptance * Accepted **RoHS Declaration *** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature**

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

Item/SubItem				Homogeneous	Walada 4	Unit of			Substance Category			Out of our o	CAC	Exempt	Weight	Unit of Measure	Tolerance		DDM
	Name		Material	Weight	Measure		Level	Substance Category			Substance	CAS	-				+	PPM	
+1 -1	Die	+M -I	Doped silicon	0.0864	mg	+C -(Supplier		+S	-s	Si	7440-21-3		0.0864	mg		:	38,357	
+1 -1	Substrate strip	+M -	SGP1610P4	1.183	mg	+C -(Supplier		+S	-s	Bismaleimide Triazine r	105391-33-1		0.1606	mg		-	71,303	
				•					+S	-S	Inorganic Filler	21645-51-2		0.0803	mg			35,652	
									+S	-S	Continuous Filament Fi	65997-17-3		0.1606	mg			71,303	
									+S	-S	Copper	7440-50-8		0.4015	mg			178,25	
									+S	-S	Acrylic Esters	26376-86-3		0.0932	mg			41,378	
									+S	-S	Organic black dye			0.0016	mg			693	
									+S	-S	Barium sulfate	7727-43-7		0.0941	mg			41,778	
									+S	-S	Talc	14807-96-6		0.0079	mg			3,496	
									+S	-S	Silica crystalline	7631-86-9		0.0081	mg			3,586	
									+S	-S	Activator	Proprietary		0.0163	mg			7,243	
									+S	-S	Amine compound	Proprietary		0.001	mg			431	
									+S	-S	Defoamer	Proprietary		0.007	mg			3,118	
									+S	-S	Dipropyl glycol dinitrate	112-15-2		0.0313	mg			13,911	
									+S	-S	Heavy aromatic solvent	64742-94-5		0.0322	mg			14,277	
									+S	-S	Naphthalene	91-20-3		0.0019	mg			829	
						+C -(В	Nickel (external applic	+S	-S	Nickel	7440-02-0		0.0071	mg			3,150	
						+C -(Supplier		+S	-S	Pd	7440-05-3		0.0698	mg			30,979	
									+S	-s	Au	7440-57-5		0.0083	mg			3,675	
+1 -1	Bonding wire	+M -	Cu/Pd coated	0.007	mg	+C -0	Supplier		+S	-s	Cu	7440-50-8		0.0068	mg		\neg	3,013	
				•					+S	-S	Pd	7440-05-3		0.0002	mg			77	
+1 -1	Molding compound	+M -	EME-G760L	0.945	mg	+C -0	Supplier		+S	-s	Silica (Amorphous) A	60676-86-0		0.7326	mg		\neg	325,22	
									+S	-s	Silica (Amorphous) B	7631-86-9		0.0756	mg			33,571	

+8 -8	Epoxy resin	Proprietary	0.0750		Τ		00 574				
+3 -3	Epoxy resin	Proprietary	0.0756	mg			33,571				
+8 -8	Phenol resin	Proprietary	0.0284	mg			12,589				
+8 -8	Metal Hydroxide	Proprietary	0.0284	mg			12,589				
+5 -5	С	1333-86-4	0.0047	mg			2,098				
+I -I Die attached epoxy +M -M 8006NS	0.021 mg +0	C -C Supplier		+8	-s	Alumir	num oxide	1344-28-1	0.0071	mg	3,155
				+5	-S	Diethy	lene glycol mono	112-15-2	0.0071	mg	3,155
				+5	s -s	Ероху	resin	Proprietary	0.0059	mg	2,598
				+5	s -s	Amine	ı	Proprietary	0.0008	mg	371
+M -M 8008MD	0.01 mg +0	C -C Supplier		+8	-S	Ag		7440-22-4	0.0068	mg	3,017
				+5	s -s	Rubbe	r modified epoxy	Proprietary	0.0008	mg	366
				+5	s -s	Diethy	lene glycol mono	112-15-2	0.0008	mg	366
				+5	s -s	BMI re	sin	Proprietary	0.0003	mg	137
				+5	s -s	Carbo	nic ester	Proprietary	0.0003	mg	137
				+5	S -S	Acryla	te oligomer	Proprietary	0.0003	mg	137
				+5	S -S	Ероху	resin	Proprietary	0.0006	mg	274
				+5	s -s	Amine		Proprietary	0.0003	mg	137