



Material Composition Declaration

© Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.

This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.

Adobe Reader version 7.0.5 is required to complete this declaration.

1752-2 1.1	IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x	Form Type * Distribute	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informat
------------	--	---------------------------	--

Supplier Information

Company Name * SEMTECH CORPORATION	Company Unique ID 00-847-9941	Unique ID Authority DUNS	Response Date * 2016-07-18	Response Document ID				
Contact Name * Roya Motamedi	Title - Contact Supervisor, QA Product Support	Phone - Contact * 805-498-2111	Email - Contact * rmotamedi@semtech.com	Duplicate Contact -> Authorized Representative				
Authorized Representative * Roya Motamedi	Title - Representative Supervisor, QA Product Support	Phone - Representative * 805-498-2111	Email - Representative * rmotamedi@semtech.com	Supplier Comments or URL for Additional Information				
Requester Item Number	Mfr Item Number	Mfr Item Name	Effective Date	Version	Manufacturing Site	Weight *	UOM	Unit Type
	SC2599ULTRC	Low Voltage DDR Termination R			Malaysia	7.87	mg	Each
Alternate Recommendation				Alternate Item Comments				

Manufacturing Process Information

Terminal Plating / Grid Array Material	Terminal Base Alloy	J-STD-020 MSL Rating	Peak Process Body Temperature	Max Time at Peak Temperature	Number of Reflow Cycles
Matte Tin (Sn)	CU Alloy	1	260 C	30 seconds	3

Comments
SC2599ULTRC is REACH-compliant product, per EU Regulation EC1907/2006 to include recent addition of SVHC candidate list of substances in June 2016.

Save the fields in this form to a file

Export Data

Import fields from a file into this form

Import Data

Clear all of the fields on this form

Reset Form

Lock the fields on this form to prevent changes

Lock Supplier Fields

RoHS Material Composition Declaration

Declaration Type *

Detailed

RoHS Directive 2002/95/EC **RoHS Definition:** Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium

Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a RoHS restricted substance?) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.

RoHS Declaration * 1 - Item(s) does not contain RoHS restricted substances per the definition above

Supplier Acceptance * Accepted

Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.

Declaration Signature

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

+I	-I	Item/SubItem Name		+M	-M	Homogeneous Material	Weight	Unit of Measure	+C	-C	Level	Substance Category	+S	-S	Substance	CAS	Exempt	Weight	Unit of Measure	Tolerance		PPM
		-	+																			
+I	-I	Lead frame		+M	-M	C7025 AgCu	3.78	mg	+C	-C	Supplier		+S	-S	Copper	7440-50-8		3.65	mg			463,92
													+S	-S	Iron	7439-89-6		0.085	mg			10,836
									+C	-C	A	Lead/Lead Compound	+S	-S	Lead	7439-92-1		0	mg			14
									+C	-C	Supplier		+S	-S	Phosphorus	7723-14-0		0.001	mg			115
													+S	-S	Zinc	7440-66-6		0.005	mg			610
													+S	-S	Silver	7440-22-4		0.038	mg			4,803
+I	-I	Die		+M	-M	Silicon Chip	0.18	mg	+C	-C	Supplier		+S	-S	Si	7440-21-3		0.18	mg			22,871
+I	-I	Die attachmaterial		+M	-M	QMI519	0.13	mg	+C	-C	Supplier		+S	-S	Silver	7440-22-4		0.1	mg			13,297
													+S	-S	Carbocyclic Acrylate	Proprietary		0.01	mg			1,651.8
													+S	-S	Bismaleimide resin	Proprietary		0.004	mg			495.55
													+S	-S	2-preponoic acid, 2-met	68586-19-6		0.004	mg			495.55
													+S	-S	Additive	Proprietary		0.004	mg			495.55
													+S	-S	Dicumlyl peroxide	80-43-3		0.001	mg			82.59
+I	-I	Wire		+M	-M	Copper (Pd coat)	0.16	mg	+C	-C	Supplier		+S	-S	Cu	7440-50-8		0.16	mg			19,974
													+S	-S	Pd	7440-05-3		0.0028	mg			355.78
+I	-I	Encapsulation		+M	-M	EME-G770HCD	3.44	mg	+C	-C	Supplier		+S	-S	Silica Fused	60676-86-0		3.22	mg			409,56
													+S	-S	Epoxy resin	Proprietary		0.1	mg			13,113
													+S	-S	Phenol resin	Proprietary		0.1	mg			13,113
													+S	-S	Carbon black	1333-86-4		0.01	mg			1,311.3
+I	-I	Lead finish		+M	-M	Tin alloy	0.18	mg	+C	-C	Supplier		+S	-S	Tin	7440-31-5		0.18	mg			22,871