ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES®	© Co	terial Compo pyright 2005. IPC, Bannoc nternational and Pan-Ameri	kburn, Illinois	. All rights reserv	tion with lower	level p	arts, the	declaration	encomp	asses all lo		terials for	which th	e item is an assembly ne manufacturer has declaration.		
1752-2 1.1	2 1.1 IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x					Form Type * Distribute			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informa							
Supplier Information																
Company Name *	Company Unique ID		Unique ID Au	Response Date *			Re	Response Document ID								
SEMTECH CORPORATION	ON	00-847-9941		DUNS	2017-0	3-01										
Contact Name *		Title - Contact		Phone - Cor	Email - Contact *				Donalisa	-1- 011	A 41-	:I D -				
Jeffrey Gabrielson		QA Customer Suppo	rt Speciali	805-498-211	jgabrielson@semtech.com			om	Duplica	ate Contact	-> Autho	orizea Re	epresentative			
Authorized Representative *		Title - Representative	Э	Phone - Rep	Email - Representative *			* Sı	pplier Con	nments or UR	L for Ad	ditional Ir	nformation			
Jeffrey Gabrielson		QA Customer Suppo	ort Speciali	805-498-211	1	jgabrie	elson@s	emtech.c	om							
Requester Item Number		Mfr Item Number		Mfr Item Name	Effective Date V		Version	Manufact	uring Site	Weight *	U	OM	Unit Type			
		SC4612STRT		WIDE INPUT				Malaysia		104.83	m	g	Each			
Alternate Recommendation					Alternate Item C			ments	<u> </u>							
Manufacturing Proce	ss In	formation														
Terminal Plating / Grid Array Material Term			Terminal B	ase Alloy	J-STD-020 MSL Ra	ating	Peak Process Body Tempe		Temperati	ature Max Time at Peak Tem		nperature	perature Number of Reflow C			
,			CU Alloy	,	1			2	260 C		30 se		3			
Comments SC4612STRT is REACH-	-com _l	oliant product, per E	U Regula	tion EC1907/	2006 to include re	ecent a	ddition o	of SVHC o	candidat	e list of su	ubstances in	January	, 2017.			

* Required Field

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type *** Detailed Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a ?RoHS restricted substance?) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier?s liability and the Company?s remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply. 1 - Item(s) does not contain RoHS restricted substances per the definition above Supplier Acceptance * Accepted **RoHS Declaration *** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature**

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

Item/SubItem			Homogeneous Material	Weight	Unit of Measure		Level	Substance Category			Out of our o	CAS	Exempt	Weight	Unit of Measure	Tolerance		PPM
	Name										Substance	CAS				-	+	PPM
+1 -1	Leadframe	+M -M	Ag plated Cu C1	90.00779	mg	+C -C	Supplier		+S	-S	Copper (Remaining)	7440-50-8		7.5243	mg		-	71,776
									+S	-S	Iron (2.1~2.6%)	7439-89-6		0.1757	mg			1,676
									+S	-S	Lead (0.01max)	7439-92-1		0.0023	mg			2.23
									+S	-S	Phophorus (0.015~0.15°	%7723-14-0		0.00186	mg			17.83
									+S	-S	Zinc (0.05~0.20%)	7440-66-6		0.00989	mg			94.37
		_							+S	-S	Silver (0.5~1.5%)	7440-22-4		0.0779	mg			743.11
+1 -1	Die	+M -M	Silicon Chip	0.38	mg	+C -C	Supplier		+S	-S	Si	7440-21-3		0.38	mg		;	3,624.9
+1 -1	Die Attach material	+M -M	QMI 519	0.55	mg	+C -C	Supplier		+S	-S	Silver (80 - 100%)	7440-22-4		0.44275	mg		4	4,223.5
									+S	-s	Carbocyclic Acrylates (Proprietary		0.055	mg			524.66
									+S	-s	Bismaleimide resin (1-1	Proprietary		0.0165	mg			157.4
									+S	-s	2-preponoic acid, 2-met	68586-19-6		0.0165	mg			157.4
									+S	-s	Additive (1-10%)	Proprietary		0.0165	mg			157.4
		_							+S	-S	Dicumlyl peroxide (0.1 -	80-43-3		0.00275	mg			26.23
+1 -1	Wire	+M -M	Gold	0.29	mg	+C -C	Supplier		+S	-S	Au	7440-57-5		0.28997	mg		2	2,766.1
	-								+S	-s	Others	-		0.00003	mg			0.28
+1 -1	Lead Finish	+M -M	Alloy	1.45	mg	+C -C	Supplier		+S	Ş-	Sn	7440-31-5		1.44985	mg			13,830
	-								+S	-s	Others	-		0.00015	mg			1.38
+1 -1	Encapsulation	+M -M	CEL8240HF10	94.37	mg	+C -C	Supplier		+S	Ş-	Epoxy Resin-1 (0.5-6%)	Proprietary		1.8311	mg		:	27,006
		_							+S	-S	Epoxy Resin-2 (1-5%)	Proprietary		2.8311	mg			27,006
									+S	-s	Phenol resin (3-6%)	Proprietary		4.24665	mg			40,509
									+S	-s	Silica (82-94%)	60676-86-0		82.385	mg			785,89
									+S	-s	Carbon Black (0.2%)	1333-86-4		0.18874	mg			1,800.4
									+S	-s	Others (max2%)	-		1.8874	mg			18,004