ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES®	© Co	terial Compo pyright 2005. IPC, Bannoo nternational and Pan-Ameri	kburn, Illinois	. All rights reserv	tion with lower	level p	arts, the	declaration	n encom	passes a	ll lower		rials for	which th	e item is an assembly ie manufacturer has eclaration.		
1752-2 1.1	IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x						Form Type * Distribute			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informa							
Supplier Information																	
Company Name * Com		Company Unique ID		Unique ID Au	Response Date *			F	Response Document ID								
SEMTECH CORPORATION		00-847-9941		DUNS	2014-0)5-27											
Contact Name *		Title - Contact		Phone - Con	Email - Contact *				D	F4-	0	۸ دا ـ ـ ـ	-:ID-				
Roya Motamedi		QA Customer Servic	e Specialis	805-389-274	rmotamedi@semtech.com			om	Dup	licate	Contact -	> Autho	rizea Re	presentative			
Authorized Representative *		Title - Representative	е	Phone - Rep	Email - Representative *			* 5	Supplier Comments or URL for Additional Information								
Roya Motamedi		QA Customer Service	e Specialis	805-389-274	rmotamedi@semtech.com			om									
Requester Item Number		Mfr Item Number		Mfr Item Name	Effective Date		Version Manufa		facturing Site		Weight *	UC	OM	Unit Type			
		SC508ULTRT		46V EcoSpee	¢			Malaysia			16.5	mg]	Each			
Alternate Recommend	ation					Altern		Alternate	e Item Comments		'						
Manufacturing Proce	ss In	formation				•											
Terminal Plating / Grid Array Material		Terminal Base Alloy		J-STD-020 MSL Rating		Peak Process Body Tempe		Tempera	erature Max Time at Peak T		Peak Temp	mperature Number		of Reflow Cycles			
Matte Tin (Sn)			CU Alloy		1			2	260 C		30 so		econds 3				
Comments SC508ULTRT is REACH	l-com	pliant product, per	EU Regula	ntion EC1907	/2006 to include ı	recent	addition	of SVHC	candid	ate list o	of subs	tances in l	Decem	ber 2013			

Form enabled by Adobe

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type *** Detailed Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a ?RoHS restricted substance?) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier?s liability and the Company?s remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply. 1 - Item(s) does not contain RoHS restricted substances per the definition above Supplier Acceptance * Accepted **RoHS Declaration *** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature**

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

	Item/SubItem		Homogeneous	\A/a:la4	Unit of		Laval	Substance Category			Substance	CAS	Fuerent	Wajaht	Unit of	Tolerance		DDM
	Name		Material	Weight	Measure		Level	Substance Category			Substance	CAS	Exempt	Weight	Measure	-	+	PPM
+1 -1	Lead frame	+M -M	Cu C7025 Ag pla	6.22	mg	+C -C	Supplier		+S	-S	Cu	7440-50-8		5.97	mg			361,98
									+S	-S	Fe	7439-89-6		0.0012	mg			75.39
						+C -C	A	Lead/Lead Compound	+S	-S	Lead	7439-92-1		0.0001	mg			3.77
						+C -C	В	Nickel (external applic	+S	-s	Nickel	7440-02-0		0.14	mg			8,594.9
						+C -C	Supplier		+S	-s	Zn	7440-66-6		0.001	mg		- [75.39
							•	•	+S	-s	Manganese	7439-96-5		0.0002	mg			15.08
									+S	-s	Si	7440-21-3		0.03	mg			1,960.2
									+S	-s	Mg	7439-95-4		0.01	mg			490.06
									+S	-s	Ag	7440-22-4		0.06	mg			3,769.7
+1 -1	Die	+M -M	Doped Silicon	0.9	mg	+C -C	Supplier		+S	-S	Si	7440-21-3		0.896	mg		į	54,272
									+S	-S	Others	Proprietary		0.005	mg			272.73
+1 -1	Die attach material	+M -M	QMI519 Conduct	0.36	mg	+C -C	Supplier		+S	-\$	Ag	7440-22-4		0.306	mg			18,545
									+S	-s	Acrylates	Proprietary		0.02	mg			1,090.9
									+S	-S	Proprietary Bismaleimic	Proprietary		0.018	mg			1,090.9
									+S	-S	Additive	Proprietary		0.018	mg			1,090.9
+1 -1	Wire bonding	+M -M	Gold	0.16	mg	+C -C	Supplier		+S	-S	Au	7440-57-5		0.16	mg		!	9,696
									+S	-S	Others	Proprietary		0.00002	mg			0.97
+1 -1	Lead Finish	+M -M	Tin Alloy	0.59	mg	+C -C	Supplier		+S	-S	Sn	7440-31-5		0.59	mg			35,754
	-	•	-				-		+S	-s	Others	Proprietary		0.00006	mg			3.58
+1 -1	Encapsulation	+M -M	EME-G770HC Ep	8.27	mg	+C -C	Supplier		+S	-S	Silica Fused	60676-86-0		7.75	mg			469,63
									+S	-s	Epoxy Resin	Proprietary		0.25	mg			15,036
									+S	-s	Phenol Resin	Proprietary		0.25	mg			15,036
									+S	-s	Carbon Black	1333-86-4		0.02	mg			1,503.6